

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

VELIND Antistatikspray 300ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Aerosol with antistatic effect

Uses advised against

No information available. Benutzung ausschließlich gemäß Verwendungszweck

1.3. Details of the supplier of the safety data sheet

| | | |
|-------------------------|-------------------------|-----------------------------------|
| Company name: | VELIND Aerosol GmbH | |
| Street: | Passower Chaussee 111 | |
| Place: | D-16303 Schwedt/O | |
| Telephone: | +49 33 32 / 4 50 88 - 0 | Telefax: +49 33 32 / 4 50 88 - 30 |
| e-mail: | info@velind.de | |
| Contact person: | Witt | Telephone: 18 |
| e-mail: | qs@velind.de | |
| Internet: | www.velind.de | |
| Responsible Department: | QS | |

1.4. Emergency telephone

Emergency Poison Center / GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: +49 3 61 / 7 30 73 -0

number:**Further Information**Emergency - Phonecalls to +49 (0) 33 32 / 4 50 88 16
(during office-hours from 8.00 a.m. to 4.00 p.m.)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Dam. 1

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

propan-2-ol; isopropyl alcohol; isopropanol

Poly(oxy-1,2-ethanediyl), .alpha.-phosphono-.omega.-hydroxy-, C12-14 alkyl ethers, dipotassium salts

Signal word: Danger

Pictograms:



according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 2 of 11

Hazard statements

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H336 | May cause drowsiness or dizziness. |

Precautionary statements

| | |
|----------------|--|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P501 | With correct and proper use, and under normal conditions, not required. |

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aerosol

Hazardous components

| CAS No | Chemical name | Quantity |
|------------|--|--------------|
| | EC No | |
| | Index No | |
| | REACH No | |
| | Classification according to Regulation (EC) No. 1272/2008 [CLP] | |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | 35 - < 40 % |
| | 200-661-7 | 603-117-00-0 |
| | 01-2119457558-25 | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 | |
| 72828-57-0 | Poly(oxy-1,2-ethanediyl), .alpha.-phosphono-.omega.-hydroxy-, C12-14 alkyl ethers, dipotassium salts | 5 - < 10 % |
| | | |
| | Eye Dam. 1, Skin Sens. 1; H318 H317 | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 3 of 11

After inhalation

When in doubt or if symptoms are observed, get medical advice. Provide fresh air. Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Not applicable, because aerosol.

If it does, consult a doctor immediately and show him box or label.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur::

Intoxication. unconsciousness. Headache. drowsiness. Dizziness. Depression of the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This information is not available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), alcohol resistant foam. dry extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Contains gas under pressure; may explode if heated. (H280) Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide
Carbon dioxide.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Remove according to the regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 4 of 11

drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Collect in closed containers for disposal. Ventilate affected area.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Keep away from hot surfaces. Read label before use. Observe in addition any national regulations!

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Maximum storage temperature: 50°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Keep away from: Oxidizing agents. strong alkalis. Strong acid.

Further information on storage conditions

Fire class: C

7.3. Specific end use(s)

Aerosol with antistatic effect

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 5 of 11

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|-------------|-----|-------------------|-----------|---------------|--------|
| 106-97-8 | Butane | 600 | 1450 | | TWA (8 h) | WEL |
| | | 750 | 1810 | | STEL (15 min) | WEL |
| 67-63-0 | Propan-2-ol | 400 | 999 | | TWA (8 h) | WEL |
| | | 500 | 1250 | | STEL (15 min) | WEL |

DNEL/DMEL values

| CAS No | Substance | Exposure route | Effect | Value |
|--------------------------|---|----------------|----------|-----------------------|
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | |
| Consumer DNEL, long-term | | oral | systemic | 26 mg/kg bw/day |
| Worker DNEL, long-term | | dermal | systemic | 888 mg/kg bw/day |
| Consumer DNEL, long-term | | dermal | systemic | 319 mg/kg bw/day |
| Worker DNEL, long-term | | inhalation | systemic | 500 mg/m ³ |
| Consumer DNEL, long-term | | inhalation | systemic | 89 mg/m ³ |

PNEC values

| CAS No | Substance | Value |
|--|---|------------|
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | |
| Freshwater | | 140,9 mg/l |
| Marine water | | 140,9 mg/l |
| Freshwater sediment | | 552 mg/kg |
| Marine sediment | | 552 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 2251 mg/l |
| Soil | | 28 mg/kg |

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaust at critical locations. Exposure controls / Personal protection equipment

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. When using do not eat, drink, smoke, sniff. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 6 of 11

specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber). Butyl rubber.

Thickness of glove material: 0,7 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

Protect skin by using skin protective cream. Set out skin protection guidelines.

Apply skin care products after work.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|------------------------------------|
| Physical state: | Aerosol, Active component: flüssig |
| Colour: | colourless |
| Odour: | characteristic |

Test method

| | |
|-----------|----------------|
| pH-Value: | not determined |
|-----------|----------------|

Changes in the physical state

| | |
|--|-----------------------------|
| Melting point: | not determined |
| Initial boiling point and boiling range: | not determined |
| Flash point: | >12°C (Active component) °C |

Flammability

| | |
|--------|----------------|
| Solid: | not applicable |
| Gas: | not applicable |

Explosive properties

not explosive. In use, may form flammable/explosive vapour-air mixture.

| | |
|-------------------------|----------------|
| Lower explosion limits: | 1,4 vol. % |
| Upper explosion limits: | 12 vol. % |
| Ignition temperature: | not determined |

Auto-ignition temperature

| | |
|--------|----------------|
| Solid: | not applicable |
| Gas: | not applicable |

| | |
|----------------------------|----------------|
| Decomposition temperature: | not determined |
|----------------------------|----------------|

Oxidizing properties

Not oxidising.

| | |
|------------------|----------------|
| Vapour pressure: | not determined |
|------------------|----------------|

| | |
|---------------------|--------------------------------|
| Density (at 20 °C): | 0,858 (Active component) g/cm³ |
|---------------------|--------------------------------|

| | |
|---------------|----------------|
| Bulk density: | not applicable |
|---------------|----------------|

| | |
|-------------------|------------------------------------|
| Water solubility: | easily soluble. (Active component) |
|-------------------|------------------------------------|

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 7 of 11

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:

not determined

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

Solid content:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. The product has not been tested.

10.2. Chemical stability

Stable with proper storage and handling.

10.3. Possibility of hazardous reactions

No decomposition if used as intended

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Refer to chapter 7.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on naked flames or any incandescent material.

Heating causes rise in pressure with risk of bursting. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

10.6. Hazardous decomposition products

Refer to chapter 5.

No decomposition if used as intended

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

Mixture not tested. There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

| CAS No | Chemical name | | | | |
|---------|---|------------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | | |
| | oral | LD50 >2000 mg/kg | Rat | | |
| | dermal | LD50 >2000 mg/kg | Rabbit | | |
| | inhalative (4 h) vapour | LC50 >20 mg/l | Rat | | |

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 8 of 11

Irritation and corrosivity

Causes serious eye damage.
 Skin corrosion/irritation: Based on available data, the classification criteria are not met.
 There are no data available on the mixture itself.

Sensitising effects

May cause an allergic skin reaction.
 There are no data available on the mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
 No data available

STOT-single exposure

May cause drowsiness or dizziness. ((propan-2-ol; isopropyl alcohol; isopropanol))

STOT-repeated exposure

Based on available data, the classification criteria are not met.
 No data available

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Practical experience

Observations relevant to classification

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

Further information

Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Mixture not tested. There are no data available on the preparation/mixture itself.

| CAS No | Chemical name | | | | | |
|---------|---|-----------------|-----------|-------------------------|--------|--------|
| | Aquatic toxicity | Dose | [h] [d] | Species | Source | Method |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | | | |
| | Acute fish toxicity | LC50 >100 mg/l | 96 h | Pimephales promelas | | |
| | Acute algae toxicity | ErC50 >100 mg/l | | Scenedesmus subspicatus | | |
| | Acute crustacea toxicity | EC50 >100 mg/l | 48 h | Daphnia magna | | |

12.2. Persistence and degradability

The product has not been tested. No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 9 of 11

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Mixture not tested.
There are no data available on the preparation/mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. The waste codes are recommendations based on the scheduled use of this products. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)
According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of used product

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Recommendation: Dispose of waste according to applicable legislation. E.g. Dispose of contents/container to industrial incineration plant. Or: Dispose of this material and its container to hazardous or special waste collection point.
Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 10 of 11

14.3. Transport hazard class(es):

2

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Marine transport (IMDG)

14.1. UN number:

UN1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2, see SP63

Special Provisions:

63, 190, 277, 327, 344, 959

Limited quantity:

See SP277

EmS:

F-D, S-U

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

no

14.6. Special precautions for user

Warning: Flammable gases. Persons employed in transporting dangerous goods must be trained. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

Other applicable information

Minimum amount regulations: < 1 litre

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

Information according to 2012/18/EU (SEVESO III):

P3a FLAMMABLE AEROSOLS

Additional information

Labelling for contents according to regulation (EC) No 648/2004, annex 7: No. Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D):

2 - water contaminating

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Antistatikspray 300ml

Revision date: 01.06.2017

Product code: 21058

Page 11 of 11

Additional information

Not subject to regulation Regulation (EC) No 648/2004 (Detergents regulation).

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,14,15,16.

These details refer to the products as it is delivered.

Notice the directions for use on the label.

* Data changed compared with the previous version

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H229 | Pressurised container: May burst if heated. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)