

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VELIND Glasglanz mit Kraftschaum

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

Uses advised against

No information available. Use(Usage) exclusively according to labelled intended purpose!

1.3. Details of the supplier of the safety data sheet

Company name:	VELIND Aerosol GmbH	
Street:	Passower Chaussee 111	
Place:	D-16303 Schwedt/O	
Telephone:	+49 33 32 / 4 50 88 - 0	Telefax: +49 33 32 / 4 50 88 - 30
e-mail:	info@velind.de	
Contact person:	Witt	Telephone: 18
e-mail:	qs@velind.de	
Internet:	www.velind.de	
Responsible Department:	QS	

1.4. Emergency telephone

GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und

number: Thüringen: +49 3 61 / 7 30 73 -0

Further Information

Emergency - Phonecalls to +49 (0) 33 32 / 4 50 88 16
(during office-hours from 8.00 a.m. to 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Aerosol: Aerosol 1
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 2 of 13

P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aerosol

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			5 - < 10 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
64-17-5	ethanol, ethyl alcohol			1 - < 5 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319 EUH066			
1336-21-6	ammonia ... %			< 1 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Met. Corr. 1, Skin Corr. 1B, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H290 H314 H335 H400 H410			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

5 % - < 15 % aliphatic hydrocarbons, perfumes (Limonene).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.

After inhalation

Provide fresh air. Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 3 of 13

ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Not applicable, because aerosol. If it does, consult a doctor immediately and show him box or label.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur::

Intoxication. unconsciousness. Headache. drowsiness. Dizziness. Depression of the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This information is not available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Extinguishing powder. alcohol resistant foam. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Contains gas under pressure; may explode if heated. (H280) Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide Carbon dioxide.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Remove according to the regulations.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.

Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protection equipment. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area. Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 4 of 13

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not pierce or burn, even after use. Do not breathe gas/fumes/vapour/spray. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Keep away from hot surfaces. Read label before use. Observe in addition any national regulations!

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Maximum storage temperature: 50°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances. Keep away from: Oxidizing agents. strong alkalis. Strong acid.

Further information on storage conditions

Fire class: C

7.3. Specific end use(s)

SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 5 of 13

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
64-17-5	ethanol, ethyl alcohol			
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	950 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
1336-21-6	ammonia ... %			
Worker DNEL, acute		dermal	systemic	6,8 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	6,8 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	47,6 mg/m ³
Worker DNEL, acute		inhalation	local	36 mg/m ³
Worker DNEL, long-term		inhalation	systemic	47,6 mg/m ³
Worker DNEL, long-term		inhalation	local	14 mg/m ³
Consumer DNEL, acute		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	68 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, acute		inhalation	local	7,2 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	23,8 mg/m ³
Consumer DNEL, long-term		inhalation	local	2,8 mg/m ³
Consumer DNEL, acute		oral	systemic	6,8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	6,8 mg/kg bw/day

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/l
Marine sediment		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
1336-21-6	ammonia ... %	
Freshwater		0,0011 mg/l
Marine water		0,0011 mg/l

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Exposure controls / Personal protection equipment

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. When using do not eat, drink, smoke, sniff. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber). Butyl rubber.

Thickness of glove material: 0,7mm

Breakthrough times and swelling properties of the material must be taken into consideration.

Protect skin by using skin protective cream. Set out skin protection guidelines.

Apply skin care products after work.

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 7 of 13

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing . . With correct and proper use, and under normal conditions, not required.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol, Active component: liquid
Colour:	cloudy
Odour:	characteristic
pH-Value:	10-11 (Active component)

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	Active component: >23 °C

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

not explosive. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	1,7 vol. %
Upper explosion limits:	12 vol. %
Ignition temperature:	not determined

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

Density:	0,975 (Active component) g/cm ³
Bulk density:	not applicable
Water solubility:	easily soluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 8 of 13

Solid content:

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. The product has not been tested.

10.2. Chemical stability

Stable with proper storage and handling.

10.3. Possibility of hazardous reactions

No decomposition if used as intended

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Refer to chapter 7.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on naked flames or any incandescent material.

Heating causes rise in pressure with risk of bursting. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

10.6. Hazardous decomposition products

Refer to chapter 5.

No decomposition if used as intended

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

Mixture not tested. There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
1336-21-6	ammonia ... %				
	oral	LD50 350 mg/kg	Rat		

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 9 of 13

Irritation and corrosivity

Based on available data, the classification criteria are not met.
There are no data available on the mixture itself.

Sensitising effects

Based on available data, the classification criteria are not met.
There are no data available on the mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
There are no data available on the mixture itself. 1

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.
There are no data available on the mixture itself.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself. No data available

Practical experience

Observations relevant to classification

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

Further information

Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Mixture not tested. There are no data available on the preparation/mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 >100 mg/l		Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Chlorella vulgaris		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
1336-21-6	ammonia ... %					
	Acute fish toxicity	LC50 0,53 mg/l	96 h	Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 24 mg/l	48 h	Daphnia magna		

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 10 of 13

12.2. Persistence and degradability

The product has not been tested. No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,32
1336-21-6	ammonia ... %	-1,38

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol, ethyl alcohol	0,66		

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Avoid release to the environment. Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The waste codes are recommendations based on the scheduled use of this products. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.
(2001/118/EC, 2001/119/EC, 2001/573/EC)

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of used product

070699 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; wastes not otherwise specified

Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled. Recommendation: Dispose of waste according to applicable legislation. E.g. Dispose of contents/container to industrial incineration plant. Or: Dispose of this material and its container to hazardous or special waste collection point.
Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)

- 14.1. UN number:** UN1950
- 14.2. UN proper shipping name:** AEROSOLS
- 14.3. Transport hazard class(es):** 2

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 11 of 13

Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)

E0

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases. Persons employed in transporting dangerous goods must be trained. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

Other applicable information

Minimum amount regulations: < 1 litre

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 12 of 13

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS (SEVESO III):

Additional information

Regulation (EC) No. 648/2004 (Detergents regulation). Labelling for contents according to regulation (EC) No 648/2004, annex 7: Yes.

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1.

These details refer to the products as it is delivered.

Notice the directions for use on the label.

* Data changed compared with the previous version

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Glasglanz mit Kraftschaum

Revision date: 11.07.2019

Product code: 211951

Page 13 of 13

H410 Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)