

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

VELIND Kunststoffpflegespray 500ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Automotive Care (spray, liquid), SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

Uses advised against

No information available. Use(Usage) exclusively according to labelled intended purpose!

1.3. Details of the supplier of the safety data sheet

Company name:	VELIND Aerosol GmbH	
Street:	Passower Chaussee 111	
Place:	D-16303 Schwedt/O	
Telephone:	+49 33 32 / 4 50 88 - 0	Telefax: +49 33 32 / 4 50 88 - 30
e-mail:	info@velind.de	
Contact person:	Witt	Telephone: 18
e-mail:	qs@velind.de	
Internet:	www.velind.de	
Responsible Department:	QS	

1.4. Emergency telephone

Emergency Poison Center / GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: +49 3 61 / 7 30 73 -0

number:**Further Information**Emergency - Phonecalls to +49 (0) 33 32 / 4 50 88 16
(during office-hours from 8.00 a.m. to 4.00 p.m.)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:
Aerosol: Aerosol 1
Skin corrosion/irritation: Skin Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Aspiration hazard: Asp. Tox. 1
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Signal word: Danger

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 2 of 12

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of the Contents/container of waste according to with local/national regulations applicable legislation.

Special labelling of certain mixtures

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Aerosol

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			45 - < 50 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411 EUH066			
64-17-5	ethanol, ethyl alcohol			5 - < 10 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 3 of 12

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.

After inhalation

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Provide fresh air. Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Not applicable, because aerosol. If it does, consult a doctor immediately and show him box or label.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur:

Intoxication. unconsciousness. Headache. drowsiness. Dizziness. Depression of the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This information is not available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), alcohol resistant foam. Water spray. dry extinguishing powder. Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Contains gas under pressure; may explode if heated. (H280) Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide
Carbon dioxide.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Move undamaged containers from immediate hazard area if it can be done safely. Remove according to the regulations.

SECTION 6: Accidental release measures

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 4 of 12

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area. Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Keep away from hot surfaces. Read label before use. Observe in addition any national regulations!

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on naked flames or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Maximum storage temperature: 50°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. Keep away from: Oxidizing agents. strong alkalis.

Further information on storage conditions

Fire class: C

7.3. Specific end use(s)

Automotive Care (spray, liquid), SURFACE CLEANERS (liquid, powder, gel neat, spray neat) for consumer use

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 5 of 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	609 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
64-17-5	ethanol, ethyl alcohol			
	Worker DNEL, acute	inhalation	local	1900 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	950 mg/m ³
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, acute	inhalation	local	950 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m ³
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day

PNEC values

CAS No	Substance	Value
64-17-5	ethanol, ethyl alcohol	
	Freshwater	0,96 mg/l
	Marine water	0,79 mg/l
	Freshwater sediment	3,6 mg/l
	Marine sediment	2,9 mg/l
	Micro-organisms in sewage treatment plants (STP)	580 mg/l
	Soil	0,63 mg/kg

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 6 of 12

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation as well as local exhaustion at critical locations. Exposure controls / Personal protection equipment

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary . When using do not eat or drink. When using do not eat, drink, smoke, sniff. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves are to be worn:
 Suitable material: NBR (Nitrile rubber). Butyl rubber.
 Thickness of glove material: 0,7mm
 Breakthrough times and swelling properties of the material must be taken into consideration.
 Protect skin by using skin protective cream. Set out skin protection guidelines.
 Apply skin care products after work.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection. With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol, Active component: flüssig
Colour:	colourless
Odour:	characteristic

Test method

pH-Value:	not applicable
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	not determined

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

not explosive. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	1 vol. %
-------------------------	----------

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 7 of 12

Upper explosion limits: 9,4 vol. %

Ignition temperature: not determined

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidising.

Vapour pressure: not determined

 Density: 0,735 (Active component) g/cm³

Bulk density: not applicable

Water solubility: The study does not need to be conducted because the substance is known to be insoluble in water

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. The product has not been tested.

10.2. Chemical stability

Stable with proper storage and handling.

10.3. Possibility of hazardous reactions

No decomposition if used as intended

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Refer to chapter 7.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on naked flames or any incandescent material.

Heating causes rise in pressure with risk of bursting. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

10.5. Incompatible materials

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

10.6. Hazardous decomposition products

Refer to chapter 5.

No decomposition if used as intended

SECTION 11: Toxicological information

11.1. Information on toxicological effects

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 8 of 12

Toxicokinetics, metabolism and distribution

Mixture not tested. There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		
	inhalative (4 h) vapour	LC50 >20 mg/l	Rat		
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 6200 mg/kg	Rat	IUCLID	
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50 95,6 mg/l	Rat	RTECS	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

No data available

Sensitising effects

Based on available data, the classification criteria are not met.

No data available

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No data available

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

No data available

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Practical experience

Observations relevant to classification

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

Further information

Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 9 of 12

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Mixture not tested. There are no data available on the preparation/mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute fish toxicity	LC50 >10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >1 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 >1 mg/l	48 h	Daphnia magna		
	Crustacea toxicity	NOEC 0,17 mg/l	21 d	Daphnia magna		
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50 >2000 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 275 mg/l	72 h	Chlorella vulgaris		
	Acute crustacea toxicity	EC50 >2000 mg/l	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

The product has not been tested. No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,32

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol, ethyl alcohol	0,66		

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation. The waste codes are recommendations based on the scheduled use of this products. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 10 of 12

Waste disposal number of used product

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors
Classified as hazardous waste.

Waste disposal number of contaminated packaging

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Recommendation: Dispose of waste according to applicable legislation. E.g. Dispose of contents/container to industrial incineration plant. Or: Dispose of this material and its container to hazardous or special waste collection point.
Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 11 of 12

14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)
E0

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable gases. Persons employed in transporting dangerous goods must be trained. Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

Other applicable information

Minimum amount regulations: < 1 litre

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane

Entry 29: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional information: E2

Additional information

Labelling for contents according to regulation (EC) No 648/2004, annex 7: Yes.

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,14,15,16.

These details refer to the products as it is delivered.

Notice the directions for use on the label.

* Data changed compared with the previous version

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Kunststoffpflegespray 500ml

Revision date: 30.05.2017

Product code: 31828

Page 12 of 12

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)