

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VELIND Eis-Stop 500ml

UFI: E65U-1236-V00H-ACRH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-freeze and de-icing products

Uses advised against

No information available. Use(Usage) exclusively according to labelled intended purpose!

1.3. Details of the supplier of the safety data sheet

Company name:	VELIND Aerosol GmbH	
Street:	Passower Chaussee 111	
Place:	D-16303 Schwedt/O	
Telephone:	+49 33 32 / 4 50 88 - 0	Telefax: +49 33 32 / 4 50 88 - 30
e-mail:	info@velind.de	
Contact person:	Wallbaum	Telephone: 11
e-mail:	qs@velind.de	
Internet:	www.velind.de	
Responsible Department:	QS	

1.4. Emergency telephone number: GGIZ der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: +49 3 61 / 7 30 73 -0

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

ethanediol, ethylene glycol

Signal word: Danger

Pictograms:



Hazard statements

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H373

May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 2 of 15

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of the Contents/container of waste according to with local/national regulations applicable legislation.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:


Hazard statements

H373

Precautionary statements

P101-P102-P260-P501

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64-17-5	ethanol, ethyl alcohol			30 - < 35 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319 EUH066			
107-21-1	ethanediol, ethylene glycol			20 - < 25 %
	203-473-3	603-027-00-1	01-2119456816-28	
	Acute Tox. 4, STOT RE 2; H302 H373			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			15 - < 20 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
78-93-3	Butanone			< 1 %
	201-159-0	606-002-00-3	01-2119457290-43	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-17-5	200-578-6	ethanol, ethyl alcohol	30 - < 35 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg Eye Irrit. 2; H319: >= 50 - 100	
107-21-1	203-473-3	ethanediol, ethylene glycol	20 - < 25 %
		inhalation: LC50 = >2,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg STOT RE 2; H373: >= 10 - 100	
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	15 - < 20 %
		inhalation: LC50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
78-93-3	201-159-0	Butanone	< 1 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	

Further Information

In use, may form flammable/explosive vapour-air mixture. Inhalation causes narcotic effects/intoxication.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. First aider: Pay attention to self-protection! Move victim out of danger zone.

After inhalation

Provide fresh air. Move victim out of danger zone. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur:

Intoxication. unconsciousness. Headache. drowsiness. vomiting. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. This information is not available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam. Carbon dioxide (CO₂). Water spray. dry extinguishing powder. Water fog.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Vapours are heavier than air and will spread at floor level. Beware of reignition. Special exposure hazards arising from the substance itself, combustion products, resulting gases: Carbon monoxide Carbon dioxide.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 4 of 15

5.3. Advice for firefighters

Special protective equipment for firefighters In case of fire: Wear self-contained breathing apparatus.

Additional information

Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Remove according to the regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Provide adequate ventilation. Wear personal protection equipment. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Provide fresh air. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Ventilate affected area. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff. Keep out of the reach of children. Read label before use. Observe in addition any national regulations!

Advice on protection against fire and explosion

Protect from sunlight. Store in a well-ventilated place. Keep only in the original container in a cool, well-ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Maximum storage temperature: 50°C Further information concerning storage conditions: The floor should be leak tight, jointless and not absorbent. Ensure adequate ventilation of the storage area.

Hints on joint storage

Keep away from: Oxidizing agents. strong alkalis. Strong acid.

Further information on storage conditions

Fire class: B

7.3. Specific end use(s)

Anti-freeze and de-icing products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 5 of 15

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
78-93-3	Butan-2-one (methyl ethyl ketone)	200	600		TWA (8 h)	WEL
		300	899		STEL (15 min)	WEL
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
57-55-6	Propane-1,2-diol, particulates	-	10		TWA (8 h)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
78-93-3	Butan-2-one	butan-2-one	70 µmol/L	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 6 of 15

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol, ethyl alcohol			
Worker DNEL, acute		inhalation	local	1900 mg/m ³
Worker DNEL, long-term		inhalation	systemic	950 mg/m ³
Worker DNEL, long-term		dermal	systemic	343 mg/kg bw/day
Consumer DNEL, acute		inhalation	local	950 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	114 mg/m ³
Consumer DNEL, long-term		oral	systemic	87 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	206 mg/kg bw/day
107-21-1	ethanediol, ethylene glycol			
Worker DNEL, long-term		inhalation	local	35 mg/m ³
Worker DNEL, long-term		dermal	systemic	106 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	7 mg/m ³
Consumer DNEL, long-term		dermal	systemic	53 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
57-55-6	propan-1,2-diol			
Worker DNEL, long-term		inhalation	systemic	268 mg/m ³
Worker DNEL, long-term		inhalation	local	10 mg/m ³
Consumer DNEL, long-term		dermal	systemic	213 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		oral	systemic	85 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	10 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 7 of 15

PNEC values

CAS No	Substance	Value
Environmental compartment		
64-17-5	ethanol, ethyl alcohol	
Freshwater		0,96 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/l
Marine sediment		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
107-21-1	ethanediol, ethylene glycol	
Freshwater		10 mg/l
Marine water		1 mg/l
Freshwater sediment		20,9 mg/kg
Micro-organisms in sewage treatment plants (STP)		199,5 mg/l
Soil		1,53 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg
57-55-6	propan-1,2-diol	
Freshwater		260 mg/l
Marine water		26 mg/l
Freshwater sediment		572 mg/kg
Marine sediment		57,2 mg/kg
Micro-organisms in sewage treatment plants (STP)		20000 mg/l
Soil		50 mg/kg

Additional advice on limit values

Take precautionary measures against static discharges.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations. Exposure controls / Personal protection equipment

Protective and hygiene measures

When using do not eat, drink, smoke, sniff. Personal protection equipment. Contaminated work clothing should not be allowed out of the workplace. Technical ventilation of workplace.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 8 of 15

Eye/face protection

With correct and proper use, and under normal conditions, not required.
 Recommendation: Wear eye/face protection.

Hand protection

Tested protective gloves are to be worn: The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable material: NBR (Nitrile rubber). Butyl rubber. Observe Glove plan!

Thickness of glove material: 0,7mm

Breakthrough times and swelling properties of the material must be taken into consideration.

Protect skin by using skin protective cream. Observe skin protection programme.

Apply skin care products after work.

Skin protection

With correct and proper use, and under normal conditions, not required.
 Wear personal protection equipment.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at: exceeding exposure limit values. Filtering device (full mask or mouthpiece) with filter: A-P2

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	colourless	
Odour:	characteristic	
pH-Value:		4,5

Changes in the physical state

Melting point:	not determined
Boiling point or initial boiling point and boiling range:	>78 °C
Flash point:	>12 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

The product is not: Explosive. not explosive. In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	2 vol. %
Upper explosion limits:	15 vol. %

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Oxidizing properties

The product is not: oxidising.

Vapour pressure: not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 9 of 15

Density:	0,910 g/cm ³
Bulk density:	not applicable
Water solubility:	easily soluble
Solubility in other solvents	
not determined	
Partition coefficient n-octanol/water:	not determined
Relative vapour density:	not determined
Evaporation rate:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

Mixture not tested. There are no data available on the preparation/mixture itself.

10.2. Chemical stability

Stable with proper storage and handling.

10.3. Possibility of hazardous reactions

No decomposition if used as intended

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Refer to chapter 7.

Take precautionary measures against static discharges.

10.5. Incompatible materials

Refer to chapter 7.

Materials to avoid: Oxidizing agents.

10.6. Hazardous decomposition products

Refer to chapter 5.

No decomposition if used as intended

In case of fire may be liberated: Carbon monoxide. Carbon dioxide.

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

Mixture not tested. There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 10 of 15

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-17-5	ethanol, ethyl alcohol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
107-21-1	ethanediol, ethylene glycol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Mouse		
	inhalation (4 h) aerosol	LC50 >2,5 mg/l	Rat		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 >20 mg/l	Rat		
78-93-3	Butanone				
	oral	LD50 >2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Sensitising effects

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

There are no data available on the mixture itself.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (ethanediol, ethylene glycol)

There are no data available on the mixture itself.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. There are no data available on the mixture itself. No data available

Practical experience

The evaluation based on subjective human observations: May cause drowsiness or dizziness. Headache.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 11 of 15

Further information

Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

Mixture not tested. There are no data available on the preparation/mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol, ethyl alcohol					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 >100 mg/l	72 h	Chlorella vulgaris		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
107-21-1	ethanediol, ethylene glycol					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 >100 mg/l	96 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
	Fish toxicity	NOEC 15380 mg/l	7 d	Pimephales promelas		
	Crustacea toxicity	NOEC 8590 mg/l	7 d	Ceriodaphnia spec		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 >100 mg/l		Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h	Daphnia magna		
78-93-3	Butanone					
	Acute fish toxicity	LC50 >100 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 >100 mg/l	48 h			

12.2. Persistence and degradability

The product has not been tested. No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,32
107-21-1	ethanediol, ethylene glycol	-1,36

BCF

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol, ethyl alcohol	0,66		

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 12 of 15

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.7. Other adverse effects

No data available

Further information

Avoid release to the environment. Mixture not tested. There are no data available on the preparation/mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation. The waste codes are recommendations based on the scheduled use of this products. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

(2001/118/EC, 2001/119/EC, 2001/573/EC)

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

List of Wastes Code - used product

160114 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08); antifreeze fluids containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); plastic packaging

Contaminated packaging

Hazardous waste according to Directive 2008/98/EC (waste framework directive). Handle contaminated packages in the same way as the substance itself. Recommendation: Dispose of waste according to applicable legislation. E.g. Dispose of contents/container to industrial incineration plant. Or: Dispose of this material and its container to hazardous or special waste collection point.

Do not empty into drains.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1987
<u>14.2. UN proper shipping name:</u>	ALCOHOLS, N.O.S.
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 13 of 15

Transport category: 2
 Hazard No: 33
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 274 601 640D
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S.
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Labelling for contents according to regulation (EC) No 648/2004, annex 7: No.

National regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 14 of 15

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,8,9,10,13,14,15,16.

These details refer to the products as it is delivered.

Follow the instructions for use on the label.

* Data changed compared with the previous version

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Safety Data Sheet

according to Regulation (EC) No 1907/2006

VELIND Eis-Stop 500ml

Revision date: 11.06.2021

Product code: 31835

Page 15 of 15

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)